

AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

1. (Canceled)
2. (Canceled)
3. (Currently Amended) The ink jet printer as recited in claim 39 [[2]], wherein in said timing control, the timing of applying signal voltage to print said smaller dot is controlled.
4. (Canceled)
5. (Canceled)
6. (Currently Amended) The ink jet printer as recited in claim 40 [[5]], wherein said speed of ejection of said ink droplet is changed by changing a change degree in signal voltage to print said dot.
7. (Currently Amended) The ink jet printer as recited in claim 40 [[1]], wherein said ink jet printer comprising an ink jet head ejecting said ink droplet, said ink jet head being moved at a prescribed speed in a prescribed direction, and said

controller controls the printing position of said smaller dot based on the ejection speed of the ink droplet and said scanning speed.

8. (Currently Amended) The ink jet printer as recited in claim 39 [[1]] further comprising determination means for determining a direction of the printing position of said smaller dot, said controller controlling the printing position of said smaller dot according to the determination.

9. (Canceled)

10. (Canceled)

11. (Currently Amended) The ink jet printer as recited in claim 40 [[10]], wherein in said timing control, the timing of applying signal voltage to print said dot is controlled.

12. (Canceled)

13. (Canceled)

14. (Currently Amended) The ink jet printer as recited in claim 40 [[13]], wherein the speed of ejection of said ink droplet is changed by changing a change degree in signal voltage to print said dot.

15. (Currently Amended) The ink jet printer as recited in claim 40 [[9]], wherein said ink jet head is moved at a prescribed scanning speed in a prescribed direction, and said controller controls the printing position of the smoothing dots based on the ejection speed of the ink droplet and said scanning speed.

16. (Currently Amended) The ink jet printer as recited in claim 40 [[9]] further comprising determination means for determining a direction of the printing position of said smoothing dots, said controller controlling the printing position of said smoothing dots according to the determination.

17. (Canceled)

18. (Canceled)

19. (Canceled)

20. (Canceled)

21. (Canceled)

22. (Canceled)

23. (Canceled)

24. (Canceled)

25. (Canceled)

26. (Currently Amended) The ink jet printer as recited in claim 39 [[25]], wherein in said timing control, the timing of applying signal voltage to print said smoothing dot is controlled.

27. (Canceled)

28. (Currently Amended) An ink jet printer as recited in claim 40 [[27]], wherein said speed of ejection of said ink droplet is controlled by varying a change degree in signal voltage to print said smoothing dot.

29. (Currently Amended) An ink jet printer as recited in claim 41 [[24]], wherein said nozzle moves along the recording medium during a printing operation, and said distance between the smoothing dot and the center of the image forming dot adjacent to said smoothing dot is controlled based on the ejection speed of the ink droplet and the moving speed of the nozzle.

30. (Canceled)

31. (Canceled)

32. (Canceled)

33. (Canceled)

34. (Currently Amended) The ink jet printer of claim 39 [[1]], wherein said smaller dot and said image forming dot are ejected from said single nozzle during a single scan.

35. (Currently Amended) The ink jet printer of claim 40 [[9]], wherein the smoothing droplets and image forming droplets are ejected from the single nozzle during a single scan.

36. (Canceled)

37. (Currently Amended) The ink jet printer of claim 41 [[24]], wherein the ~~nozzle is for ejecting ink droplets of different sizes during~~ the smoothing droplets and image forming droplets are ejected from the single nozzle during a single scan.

38. (Canceled)

39. (New) An ink jet printer ejecting a plurality of kinds of ink droplets of different sizes from a single nozzle depending upon data to be printed, thereby forming an image on a prescribed recording medium using dots of sizes corresponding to the sizes of the ink droplets, comprising:

an ink jet head for ejecting an image forming droplet and a smoothing droplet from a single nozzle based on data to be printed, the smoothing droplet being smaller than the image forming droplet, thereby printing dots of sizes corresponding to the sizes of the ink droplets on a prescribed recording medium;

a smoother for performing a smoothing process using the smoothing droplet to form a smoothing dot, wherein the distance between a center of the smaller size smoothing dot and a center of the image forming dot is smaller than the pitch of the image forming dot, and

a controller for controlling the smoother, thereby maintaining constant the speed of ejection of the ink droplet forming the smoothing dot and changing the timing of ejection of the ink droplet forming the smoothing dot.

40. (New) An ink jet printer ejecting a plurality of kinds of ink droplets of different sizes from a single nozzle depending upon data to be printed, thereby forming an image on a prescribed recording medium using dots of sizes corresponding to the sizes of the ink droplets, comprising:

an ink jet head for ejecting an image forming droplet and a smoothing droplet from a single nozzle based on data to be printed, the smoothing droplet being smaller than the image forming droplet, thereby printing dots of sizes corresponding to the sizes of the ink droplets on a prescribed recording medium;

a smoother for performing a smoothing process using the smoothing droplet to form a smoothing dot, wherein the distance between a center of the smaller size smoothing dot and a center of the image forming dot is smaller than the pitch of the image forming dot, and

a controller for controlling the smoother, thereby changing the speed of ejection of the ink droplet forming the smoothing dot in accordance with the size of the ink droplet forming the smoothing dot and changing the timing of ejection of the ink droplet forming the smoothing dot.

41. (New) An ink jet printer ejecting a plurality of kinds of ink droplets of different sizes from a single nozzle depending upon data to be printed, thereby forming an image on a prescribed recording medium using dots of sizes corresponding to the sizes of the ink droplets, comprising:

an ink jet head for ejecting an image forming droplet and a smoothing droplet from a single nozzle based on data to be printed, the smoothing droplet being smaller than the image forming droplet, thereby printing dots of sizes corresponding to the sizes of the ink droplets on a prescribed recording medium;

a smoother for performing a smoothing process using the smoothing droplet to form a smoothing dot, wherein the distance between a center of the smaller size smoothing dot and a center of the image forming dot is smaller than the pitch of the image forming dot, and

a controller for controlling the smoother, thereby changing the speed of ejection of the ink droplet forming the smoothing dot in accordance with the size of the ink droplet forming the smoothing dot and not changing the timing of ejection of the ink droplet forming the smoothing dot.